

# SHREDDER RE



Steep and Deep  
Deep Snow

A special tool for those deep snow shredders who are thirsty for big jumps and smooth landings.

## WHAT'S NEW

- Shorter and tapered tunnel
- PPS<sup>3</sup>-DS rear suspension
- LFS-DS front suspension with twin-link steering system
- Higher and more open running board design
- Blade DSS skis
- Ultra compact and lightweight deep snow seat
- Short 90 mm riser block

## PACKAGE HIGHLIGHTS

- Premium LED headlights
- E-TEC<sup>®</sup> SHOT™ starter standard
- 10.25 in. touchscreen display with BRP Connect and built-in GPS as an option
- Kashima-coated high-performance KYB shock package
- Adjustable brake lever
- Rail Reinforcements
- Ice scratchers

## SPRING OPTIONS

- Black color (850 E-TEC<sup>®</sup> Turbo R)
- Electric Starter (3700 850 engine only)



ROTAX <sup>®</sup> ENGINE	850 E-TEC <sup>®</sup> Turbo R	850 E-TEC <sup>®</sup>	600R E-TEC <sup>®</sup>
<b>Engine details</b>	Liquid-cooled, two-stroke, turbocharged, 3-D R.A.V.E.™	Liquid-cooled, two-stroke, 3-D R.A.V.E.™	
<b>Cylinders / Displacement</b>	2 - 849 cc	2 - 599.4 cc	
<b>Bore / Stroke (mm)</b>	82 x 80.4	72.3 x 73	
<b>Maximum engine speed</b>	7,900 RPM	8,100 RPM	
<b>Carburation</b>	Electronic Direct Injection with additional booster injectors	Electronic Direct Injection	
<b>Fuel type / Octane</b>	Unleaded - 95		
<b>Fuel tank (L)</b>	37	37	37
<b>Oil capacity (L)</b>	3.4	3.4	3.4

POWERTRAIN	
<b>Drive clutch</b>	pDrive™ with clickers
<b>Driven clutch</b>	QRS

DRY WEIGHT			
<b>Dry Weight (kg)</b>	220	210	197

## FEATURES

<b>Platform</b>	Radien <sup>2</sup>
<b>Headlights</b>	Premium LED
<b>Skis</b>	Blade DSS
<b>Seating</b>	Deep snow ultra compact
<b>Handlebar</b>	U-type aluminium with hooks, low grab handle
<b>Riser block height</b>	90 mm
<b>Starter</b>	SHOT Electric (spring only on 3700 850 E-TEC)

## COLOR



## DIMENSIONS

<b>Vehicle overall length*</b>	3080 mm (3700) 3200 mm (3900)
<b>Vehicle overall width</b>	1096 mm
<b>Vehicle overall height</b>	1240 mm
<b>Ski stance</b>	921 mm
<b>Available Tracks</b>	PowderMax <sup>†</sup> : 381 x 3705 x 64 mm PowderMax <sup>†</sup> X-Light: 381 x 3912 x 76 mm

## SUSPENSION

<b>Front suspension</b>	LFS-DS
<b>Front shock</b>	KYB PRO 40 EA-3 Kashima
<b>Rear suspension</b>	PPS <sup>3</sup> -DS
<b>Center shock</b>	KYB 46 Plus Kashima
<b>Rear Shock</b>	KYB PRO 46 EA-3 R Kashima

<b>Reverse</b>	RER™
<b>Brake system</b>	Brembo with adjustable lever
<b>Heated throttle lever / grips</b>	Standard
<b>Gauge type</b>	10.25 in. touchscreen (standard on 850 E-TEC Turbo R) 4.5 in. digital
<b>USB</b>	Yes, in front compartment
<b>Bumpers (Front/Rear)</b>	Std / Std

\* Vehicle overall length without snowflap.